





LED illumination for single or double-sided sign boxes

Easy to install—flexible and firm—SignBOX™ II creates the perfect grid of light for optimum even illumination. Designed for new or retrofit sign cabinets with depths over 5 inches. Available in single-sided and double-sided options.



- 6500 K is now 17% brighter
- · Bright, even illumination
- · Illuminates 5 inches from face
- Mounted on flexible straps for easy installation
- Constant Current Technology (CCT)



Specifications

Part number	Single-sided	6500 K	701946-6WS201
	Single-sided	5000 K	701946-5WS201
	Double-sided	6500 K	701946-6WD201
	Double-sided	5000 K	701946-5WD201

8.5 in × 1.0 in × 0.3 in Dimensions L × W × H

60 modules per 20 ft chain

120° Viewing angle

LEDs per module Single-sided

Double-sided

Modules per foot

12 in Coverage per row

Optimal light throw 5 to 12 inches from face

-40° C to +70° C Operating temperature

IP66 Protection class

Cuttable in 4 inch increments Special feature

Power per module Single-sided 0.90 W

> Double-sided 1.80 W

6500 K 117 lm/W **Efficacy**

> 5000 K 100 lm/W

Power capacity Per SloanLED 60 W 12 VDC power supply

> Single-sided 60 modules Double-sided 30 modules

Fastening Clamps with mechanical fasteners

20 ft (60 modules) per carton, 16 clamps included **Packaging**

Color temperatures 6500 K, 5000 K





SignBOX II

LED illumination for single or double-sided sign boxes

Specifications cont'd



Lumens per module	Single-sided	6500 K	105
	Single-sided	5000 K	90
	Double-sided	6500 K	210
	Double-sided	5000 K	180
Mounting hardware	Bracket	Bag of 10	401309-10
	Clamp	Bag of 16	410155-16
	Coupler	Bag of 10	401330-10









