ev Bri

- · Engineered for high color brilliance and translucency in back-lit signs or awnings.
- Eradication process provides substantial time and labor savings.
- It accommodates numerous graphics applications, including pressure sensitive vinyl, heat transfer, screen printing, and spray painting.Highly durable and easily cleaned.
- Tensile Strength (lbs): 275/220, Tear Strength (lbs): 70/70
- CSFM Approved, meets requirements of NFPA 701 and ASTM E84.
- Tested and recognized by Underwriters Laboratories as a sign component (UL-48 & UL-94).
- 8 year manufacturer's limited warranty.

2013-2014

78 inches wide, 20 oz. per sq. yd.

Cooley-Brite® II with Coolthane®

- Wick-resistant polyest fabric.
- Clear Coolthane top coating for extended fabric life.
 CSFM Approved, meets requirements of NFPA 701 and ASTM E84.
 Sign wick resistant polyester fabric is dielectrically weldable.
- Soft and flexible. It's craze resistant and easy to clean.
- 10 year manufacturer's limited warranty.

NOTE: When placing an order for Cooley-Brite II, please use a "C" before the style number. Ex: C2146A lvory.





2119A ORANGE 853010 (853110 CBII)

0123A SUNFLOWER 853022 (853122 CBII)

2037A YELLOW 853007

(853107 CBII)

(853111 CBII)

0606 WHITE 853004 (853104 CBII)

Lighter colors are more translucent than darker colors. Please hold the card up to the light to see how each color illuminates. Colors are representative only. Small variations in shade should be anticipated and are within commercial tolerances.



