

## Product Design

TransferRite 6592 is a lightweight saturated paper backing coated with a specially formulated latex pressure sensitive adhesive system for general-purpose use as pre-space and application tapes.

## Application

TransferRite 6592 works well with intermediate vinyl films, pre-spaced lettering < 2" high and is used for fine line striping. 6592 can also be used for smooth top-coated decals, thermal die-cuts and 4 color process printing.

## Performance Features

- ☑ The high tack adhesive is very effective for the **pick-up of small graphics**
- ☑ The saturated paper backing is **translucent** for visibility of graphics
- ☑ Lightweight product construction is **very economical**

Physical Properties	Values
Colors	White
Nominal Thickness	4.2 mils (.11 mm)
Adhesion @90°	10.5 oz/in (2.9 N/25mm)
Tensile Strength	20 lb/in (88 N/25mm)
Elongation (%)	3

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be constructed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective.

Cv6592/0816

