## We BRIGHTEN Your BRANDS

## PosterBOX 3

## Large, shallow fabric-faced light box illumination

- Bright, even illumination in large cabinets with depths as shallow as 2 inches for single-sided applications and 4 inches for double-sided applications
- Slim, edge mounted modules make installs fast and easy
- High efficiency and long life
- Built-in module spacer eliminates measuring, yielding perfect results every time

## **SPECIFICATIONS**

Part number	. Short701946-6WSRP Long701946-6WLRP	
Dimensions L × W × H	. Short9.89 in × 1.50 in Long19.73 in × 1.50 in	
Viewing angle	. 12.2° $\times$ 44.8° illumination	
LEDs per assembly	.Short3 Long6	
Color temperature (nominal)	. 6500 K	
Mimimum cabinet depth	. Single-sided2 in Double-sided4 in	
	Double-sided4 in	
Operating temperature		
Operating temperature	40° C to +70° C	
	40°C to +70°C	
Protection class	40° C to +70° C . IP66 . Short7.2 W Long14.0 W	

SloanLED Headquarters 5725 Olivas Park Drive • Ventura, California 93003 805.676.3200 • info@SloanLED.com

SloanLED Europe b.v. Overslagweg 7 • 2645 EK Delfgauw • The Netherlands

+31 88 12 44 900 • Europe@SloanLED.com

© 2017 SloanLED Rev C 2017-02-21

SloanLED.com

Power capacity <sup>1</sup>	Per SloanLED 100 W 24 VDC power supply
	Short6 modules Long6 modules
Fastening	Mechanical fasteners, Peel-n-stick (optional)
Packaging	6 assemblies per tray 5 trays per carton
Lumens per assembly	Short850
	Long1700

1 Any combination thereof not to exceed power rating of power supply.







PosterBOX™ 3 is licensed under: Patents CN200680037992.9, DE202006020673.6, NL1030161, US6932495, and US7841733; and patent applications EP06812715.8 and NL2000273. Green Signage and PosterBOX™  $are\ trademarks\ of\ Lux\ et\ Libertas\ BV.\ Sloan LED, the\ S\ logo, and\ Leaders\ in\ LED\ Technology\ are\ trademarks$ of Sloan Company, Inc.

