

We BRIGHTEN Your BRANDS



SignBOX RapidStick

Single or double-sided sign box illumination

- **NEW** Now available in 12 different sizes
- Bright, even 360-degree illumination
- Illuminates 6 inches from face
- High efficiency and long life
- Fast field retrofits with existing sockets

SPECIFICATIONS

Size (nominal)	Part number	Dimensions L × W × H	LEDs per lamp	Power per lamp	Efficacy	Power capacity per SloanLED 100 W 24 VDC power supply	Packaging Lamps per carton	Lumens per lamp
18 in	701972-6WD181	15.72 in × 2.00 in × 2.00 in	16	6.58 W	122 lm/W	12 lamps	16	802
24 in	701972-6WD241	21.72 in × 2.00 in × 2.00 in	20	8.06 W	127 lm/W	10 lamps	16	1021
30 in	701972-6WD301	27.72 in × 2.00 in × 2.00 in	28	11.06 W	129 lm/W	7 lamps	16	1430
36 in	701972-6WD361	33.72 in × 2.00 in × 2.00 in	36	13.42 W	125 lm/W	6 lamps	16	1671
42 in	701972-6WD421	39.72 in × 2.00 in × 2.00 in	44	17.64 W	127 lm/W	4 lamps	16	2232
48 in	701972-6WD481	45.72 in × 2.00 in × 2.00 in	48	19.12 W	128 lm/W	4 lamps	16	2451
60 in	701972-6WD601	57.72 in × 2.00 in × 2.00 in	64	25.70 W	127 lm/W	3 lamps	12	3253
64 in	701972-6WD641	61.72 in × 2.00 in × 2.00 in	68	27.16 W	128 lm/W	3 lamps	12	3464
72 in	701972-6WD721	69.72 in × 2.00 in × 2.00 in	76	27.66 W	129 lm/W	3 lamps	12	3558
84 in	701972-6WD841	81.72 in × 2.00 in × 2.00 in	92	36.76 W	127 lm/W	2 lamps	8	4683
96 in	701972-6WD961	93.72 in × 2.00 in × 2.00 in	104	41.23 W	129 lm/W	2 lamps	8	5311
120 in	701972-6WD1201	117.72 in × 2.00 in × 2.00 in	132	41.40 W	129 lm/W	2 lamps	8	5337

Viewing angle 360°

Color temperature (nominal) 6500 K

Optimum cabinet depth 16" deep (double-sided)

Operating temperature -40° C to +70° C

Fastening Fluorescent lampholders



SignBOX RapidStick is covered by US and foreign patents pending.

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED RevC 2016-10-19

