

CLEAR CHOICE AT60N

FILM APPLICATION TAPES

TECH DATA SHEET

AT60n consists of a matte finish, polypropylene film with excellent clarity, coated with an acrylic adhesive designed for clean pick up and transfer of all brands of cast or calendered vinyl. A unique polymerization process of acrylic adhesive assures a water-resistant and static free application tape. The stable adhesive will not build in tack level when applied to vinyl graphics for extended periods of storage.

PHYSICAL SPECIFICATIONS

Adhesive	Acrylic
Color	Transparent
Caliper <i>facestock</i>	93 microns (3.7 mils)
Adhesion to Steel*	1 - 4 N/100mm (1 - 3oz.)
Tensile	25MPa (3600psi)
Elongation	700
Shelf Life**	1 Year

FEATURES

- The excellent water resistance of the acrylic adhesive allows for wet application without leaving any adhesive residue on the vinyl.
- A static free adhesive improves the lamination process.
- Exceptional clarity to aid precise registration of multi-color overlays.
- Easy unwind eliminates exhausting application tape struggles.
- Rigid polypropylene facestock minimizes misalignment problems.
- Excellent lay flat to resist curling.
- Unique adhesive system will not build to vinyl during storage of graphics.
- Forgiving adhesive system allows the user to pull apart the tape easily, if the film accidentally folds onto itself!

APPLICATIONS

- General Purpose Sign Application Tape
- Airbrush frisket for sign painters.

WARRANTY

Tapes are only warranted to be free of defect in workmanship or materials at time of shipment. Manufacturer will replace or credit any material manufacturer deems defective. No acceptance or responsibility for loss, damage, or expense, implies or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability herewith.



RTape Corp.
6 Ingersoll Road
South Plainfield, NJ
07080
T 1-800-440-1250
www.rtape.com

RESPONSIVE
RELIABLE
RESOURCEFUL