



Scotchcal™

Product Bulletin 8915

Release C-EU, Effective July 2002

Overlamine – Ultra-Matte 8915 (ES)

Description

Advantages

- Ultra-Matte, highly durable, UV-resistant
- Reduces glare from interior lights
- For MCS™ warranted long term interior graphic

Product Line

8915 transparent

Characteristics

This information is subject to change. These values are typical for unprinted film and are not intended for use in specifications. Be sure this is the most current Product Bulletin. See **3M Related Literature** at the end of this bulletin.

Property	Description
Film	Dusted crystal, ultra-matte
Thickness (film and adhesive)	0.08 to 0.13 mm
Adhesive type and color	Pressure sensitive, clear
Liner	120 g/m ² , black kraft paper
Minimum application temperature (air and surface)	10°C
Service temperature range	–29□ to +80□ C
Shelf life	2 years after receipt from 3M (dry conditions, Temp. < 30°C)

Effective Performance Life

The performance statement is based on representative values obtained from testing. The actual performance is determined by the degree of maintenance and the extremes of exposure conditions.

Warranted Durability

The 3M™ MCS™ warranty statement for Scotchcal™ Overlamine-Ultra-Matte 8915 (ES) used to protect selected 3M™ Scotchcal™, Controltac™ and Scotchlite™ Graphic Films is based on the chosen material combination.

Please refer to the Product Bulletin of the 3M Graphic Film to obtain the detailed 3M™ MCS™ warranty statement for the chosen product construction.

Limitation of End Uses

- For interior applications only.
- Horizontal installation is not recommended or warranted.
- Specifically, we do not warrant this film for the following:
 - Graphics subjected to gasoline vapors or spills.
- Graphic removal from:
 - Existing graphics that must remain intact.

Important Notice

This bulletin provides technical information only.

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

3M Related Literature

3M offers for all products detailed technical literature. Additionally, comprehensive instruction bulletins are available describing in detail the best usage of our products.

Ask your local 3M contact or refer to local Commercial Graphics internet pages to get the most current product and/or instruction bulletins.

For Further Assistance

For help on specific questions relating to 3M Commercial Graphics products, please contact your local 3M Technical Service person or contact:

3M Laboratories (Europe)
Zweigniederlassung der 3M Deutschland GmbH
Commercial Graphics Division
Carl-Schurz-Str. 1
D-41453 Neuss
Germany
Phone +49 (0) 2131 14 3500
Fax +49 (0) 2131 14 2377

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.