We BRIGHTEN Your BRANDS

FlexiBRITE Flexible LED tubing

- Extremely flexible LED tubing
- Daytime color for red and neutral for other colors
- Optically modified silicone extrusion: UV stable, hydrocarbon insensitive, and non-fading
- Convenient mounting clips and mounting tracks
- Can be cut in the field¹

SPECIFICATIONS

Part number	. Red Kit Orange Kit Yellow Kit Green Kit	701499-0-Size 701499-Y-Size
	Blue Kit	701499-B-Size
Dimensions	Width Base width Height Lengths	0.5 in 1.0 in
In-field bends	. Radial bend	12 in
	Flat bend	1 in
Operating temperature	-40° C to $+70^\circ$ C	
Protection class	. IP66	
Power per foot	. 2.8 W	

SloanLED Headquarters 5725 Olivas Park Drive • Ventura, California 93003 805.676.3200 • info@SloanLED.com

SloanLED Europe b.v. Overslagweg 7 • 2645 EK Delfgauw • The Netherlands +31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2016 SloanLED Rev C 2016-11-02





Mounting Clip 701572-25

Mounting Track 701456-10

Power capacity 20 ft per SloanLED 60 W 12 VDC power supply			
Colors			
Mounting	ounting701572-25 Mounting Track701456-10		
Packaging			
Item description	Part number	Cut increments ¹	
Red Kit	701499-R-Size	2 in	
Orange Kit	701499-0-Size	2 in	

Red Kit	701499-R-Size	2 in
Orange Kit	701499-0-Size	2 in
Yellow Kit	701499-Y-Size	2 in
Green Kit	701499-G-Size	1 in
Blue Kit	701499-B-Size	1 in



1 All cut pieces can be used provided the cut is made on the cut line, and each 12" section has a set of wires for power hook-up.

FlexiBRITE is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504 and 7,213,941 and European Patent No. 1756471

