





Side illumination for shallow or narrow cabinets

PosterBOX™ features FanFlare™ technology that directs the light across the sign face with bright, even illumination. Designed for single-sided and double-sided sign boxes, PosterBOX can be used for new or retrofitted signs replacing fluorescent.

- Easily illuminates double-sided cabinets with 4-6 inch depths
- Side mounted module
- FanFlare lens technology projects light in a fan pattern to evenly illuminate sign face
- Constant Current Technology (CCT)



FlareShield™ on module

Specifications

Part number White (6500 K) 701946-CWPBM White (5000 K) 701946-NWPBM

Dimensions L × W × H 8.67 in × 1.74 in × 0.92 in

LEDs per module Light throw 4 ft

Module spacing Cabinet depth Center-to-center

> ≤4 in 12 in >4 in to ≤8 in 18 in

-40° C to +70° C Operating temperature

Protection class IP66

Special feature FanFlare lens technology

Power per module 6.7 W 82 lm/W **Efficacy**

Power capacity 8 modules per SloanLED 60 W 12 VDC power supply

Peel-n-stick and mechanical **Fastening**

Packaging 10 modules and FlareShields™ per carton

Color temperatures 6500 K. 5000 K

550 Lumens per module

Accessory FlareShield (401059) for shallower applications to

eliminate hot spots











