

SO600 | SOLVENT

Eco-Solvent / Solvent / Latex Backlit Matte (8.2 mil PET)

APPLICATION:

Light box graphic
Backlit trade show display
Department store display
Luminous Advertising
Bus shelter & Metro illuminated
signage

PRODUCT DESCRIPTION:

- Matte coated translucent PET backlit film
- High ink density, vivid colors with a matte coating reducing glare
- Provides outstanding image resolution with or without the light activated
- Excellent scratch and water resistancy with an advanced backside light diffusion coating
- Compatible in all eco/true solvent, UV, and latex ink printers

COMPATIBILITY:









Printer Compatibility:

Most solvent, eco-solvent, Latex, and UV Cure printing systems: Roland, Mimaki, Mutoh, Epson, HP, Vutek, CET, etc.

SPECIFICATIONS:

Caliper: 205 microns (8.2 mil)

Weight: 285a

Base material: Polyester Film

Surface: Matte

Width: 36" / 48" / 54" / 60"

Length: 30m (100 ft)

Core: 3"

TECHNICAL DATA:

Caliper: 205 micron ASTM D645

L.a.b: 85/1/-7 ANSIT

(D50/2º/Abs/No)

PRODUCT GUIDELINE:

Printing Tip:

Dry time will vary depending on ink type.

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlaminates are recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment Temperature $10^{\circ} \sim 25^{\circ} \text{C}$ ($50^{\circ} \sim 77^{\circ} \text{F}$), Relative Humidity 50% RH

Shelf Life:

One year stored in original package in recommended condition.