
Translucent Spray Paint

Lacryl 400 Series

Lacryl 400 Series is a translucent air dry acrylic lacquer for the plastic sign industry.



Features

Over 30 Standard Colors and over 3000 intermix colors.

Advantages / Benefits

Provides the durability and fade resistance required for sign coatings.

Compatible Surfaces

- Polycarbonate
- Acrylics

Associated Products / Required Products

- ZZ205 reducer to adjust viscosity and color saturation
- L490 clear or L491 colorless to adjust color intensity
- Sign Strip recommended as liquid maskant
- ZZ206 Cleaner remover for removal of overspray and paint

Lacryl 400 Series

Directions For Use

Surface Preparation:

Apply over a clean surface free of dirt, lint, water, grease or oil.

Mix Ratios:

- Dilute all colors 1:1 with ZZ205
- Dilute all whites 1:2 with ZZ205

Reducers:

- ZZ205 to adjust viscosity for spray
- ZZ206 for removal of overspray or removal of paint from reject

Spray Setup:

Air Pressure

Conventional..... 55-60 psi at the gun

HVLP..... 10 psi at cap

Pot Pressure..... 15-18 psi

Gun Setup

Siphon Feed 1.3 mm 0.050 fluid tip

HVLP..... 1.3 mm 0.050 fluid tip

Pot Pressure 1.2 mm 0.046 fluid tip

Application:

- Stir before and during use
- Apply when air, product and surface temperature are above 50°F and at least 5 above dew point
- Face must be placed in front of a light bank before applying Lacryl 400
- Remove static using Matthews 6428 Plastic Cleaner
- Apply several coats
- Change direction with each coat
- Keep gun at least 8 inches from surface
- Do 50 to 75% overlap
- Build up to desired color slowly
- If paint is not applied evenly, the color will look blotchy
- After desired color is achieved, apply white backer to eliminate “hot spots” in the finished product

Drying Time:

Dry to touch30 minutes

Dry to handle.....1 hour

Dry to remask using Sign Strip1 to 1-1/2 hours

Dry time before exposure to weather.....24 hours

Factory Pack Colors:

- Over 30 standard colors
- Custom color matching available

Total Film Build:

Translucent paint, total film build will vary with color standard.

Directions For Use

Equipment:

Conventional siphon gun

Equipment Cleaning:

Use ZZ205 or other suitable solvent.

Technical Data:

Lacryl 403 Lead Free White

VOC 5.2 lb/gal

Solids 33% by weight

Viscosity..... 35 \pm 3 seconds #2 Zahn cup

Density..... 7.65 lb/gal

Theoretical Coverage:

Lacryl 403 Lead Free White 350 sq. ft./gal @1 mil DFT

Important:

Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition.

Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use.

Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.



PH: 773/646-5900 • FAX: 773/646-3743 • www.matthewspaint.com
1701 East 122nd Street • Chicago, IL 60633

© 2015 Matthews Paint Company
Part No. L4100 04/15