ACCESSORIES AND OTHER EQUIPMENT

ACCU-STRETCH

Printing at higher, uniform tensions provides faster production speeds, improved registrations, longer screen and squeegee life, more consistent ink deposits and lower ink usage. The patented Accu-Stretch provides these benefits while eliminating complicated stretching systems, training and expensive tools. Self-equalizing stretch clamps provide uniform tension while minimizing fabric waste by enabling you to stretch directly from the fabric bolt. The modular design enables Accu-Stretch to be expanded to virtually any size and width of fabric and frame materials. Choose from any one of nine Accu-Stretch systems and add any combination of five sizes of Accu-Stretch Modular Upgrades to create a stretching system for your exact needs.



Features:

- ▶ 9 sizes of complete Accu-Stretch systems.
- ▶ 5 sizes of Accu-Stretch upgrades.
- **▶** Adjustable down to 10 x 15" (24 x 38cm).
- ➤ Infinite independent warp and weft tension controls.
- > Brace-bar pre-bows frames.
- > Self-equalizing clamps for even tension.
- > Compatible with all stretch and glue frames.
- > Reliable pneumatic design.
- > Easy-loading stretch-clamps.
- ▶ Gentle PVC coated locking bars.
- > Stretch directly from fabric bolt.

AS-4848 part CA-0116A

POWER REQUIREMENTS: AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

AS-4860 part CA-0117A Max length: 36" (91cm) Max width: 48" (122cm) Max length: 48" (122cm) Max width: 60" (142cm)

> AS-6060 part CA-0126A Max length: 60" (142cm) Max width: 60" (142cm) **POWER REQUIREMENTS:** AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

AS-3636 part CA-0107A Max length: 36" (91cm) Max width: 36" (91cm)

AS-3648 part CA-0108A

AS-3660 part CA-0109A

Max length: 36" (91cm) Max width: 60" (122cm)

POWER REQUIREMENTS: AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

Max length: 24" (61cm) Max width: 36" (91cm) **POWER REQUIREMENTS:** AIR: 110 psi (7.6 bar), 1 cfm (28 l/m) **POWER REQUIREMENTS:** AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

AS-2448 part CA-0102A

AS-2436 part CA-0101A

Max length: 24" (61cm) Max width: 48" (122cm) **POWER REQUIREMENTS:** AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

AS-2460 part CA-0103A

24


Max length: 24" (61cm) Max width: 60" (142cm) POWER REQUIREMENTS: AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)

Max length: 48" (122cm) Max width: 48" (122cm)

POWER REQUIREMENTS: AIR: 110 psi (7.6 bar), 1 cfm (28 l/m) POWER REQUIREMENTS: AIR: 110 psi (7.6 bar), 1 cfm (28 l/m)







WASH-IT

Available in two sizes, the Wash-It is ideal for developing and reclaiming your screens. Designed to work at waist height, these sinks are ergonomically built for function and comfort.

Features:

- **▶** Large screen capacity.
- > Multiple screen capacity.
- > Solid, waterproof steel construction.
- > Translucent back window.
- **≯** Adjustable screen racks.
- Easy and thorough drainage.

VACUPALLET

Press not included.

WSH-36 part 11506

Make more money by printing heat transfers, bumper stickers, decals, signs and more. Simply depress the footswitch, and the powerful vacuum motor holds flat stock securely without the use of spray adhesive Large Screen Capacity.

Dimensions (HxWxD): 72" (182cm) x 36" (91cm) x 24" (61cm)



GRIPPER

The Gripper is the answer for printing any two-ply garment where you must keep both the outer shell and inner lining from moving. It features a large 16 x 16" (41 x 41cm) print area to accommodate full sized designs.

The unique design of the Gripper frame pulls the image area taught for printing. The lock-lever system can be adjusted to firmly hold any material thickness from a running shorts to a quilted parka.



GR-1616 part 12011 Depth: 16" (41cm) Width: 16" (41cm)

25

800.778.8779 : 602.437.2305 workhorseproducts.com