

GE
Lighting

Tetra[®]

LED Lighting System

Power Supplies 2014



imagination at work



Choose the power supply that is right for your job.

We rigorously test our designs, components, products and processes to Six Sigma standards to ensure that Tetra® Power Supplies perform for years. In fact, over the past three years we've sold more than 500,000 Power Supplies with a warranty return rate of less than one percent. Our complete line of 12 or 24 volt Tetra Power Supplies include options for jobs of any size.

12 Volt Systems

Key Feature

Products Usage

GEPS12-20



Its' compact design is great for small jobs.

Tetra® miniMAX



GEPS12-60U-NA



Universal Voltage

Tetra® MAX



GEPS12-60U-GL



Global power supply
Universal Voltage

Tetra® PowerMAX



GEPS12D-60U



Dimmable power supply
0-10V Control
Universal Voltage

Tetra® miniStrip



GEPS12W-60




Rated for wet locations.

Tetra® PowerStrip



GEPSJB-60 — Can be used for Tetra Power Supplies:
GEPS12-60U-NA, GEPS12-60U-GL
GEPS24-100U-GL, GEPS12D-60U,
GEPS24D-80U, GEPS24-100U-NA



This product is intended solely for the use of non-residential signage lighting and is not intended for use in any other applications.

24 Volt Systems

Key Feature

Products Usage

GEPS24-20



Its' compact design is great for small jobs.

Tetra® PowerStrip DS



GEPS24-100U-NA



Universal Voltage

Tetra® miniStrip DS




GEPS24-100U-GL



Global power supply
Universal Voltage

Tetra® EdgeStrip



GEPS24D-80U



Dimmable power supply
0-10V Control
Universal Voltage

Tetra® Contour LS



GEPS24W-80



Rated for wet locations.

Tetra® Contour



GEPS24-180U



Can handle large
lighting jobs with/
built-in junction box
Universal Voltage

Tetra® Power Supplies — 12 Volt

SKU Description

Supports
Tetra Products SKUs

GEPS12-20

Power Supply (12VDC/20W), Input Voltage: 90-264VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2



Tetra miniMAX

GEMM71-2, GEMM50-2, GEMM41-2, GEMM32-2

GEMMRD-1, GEMMBL-1

GEMMGL-1,

GEMMPO-1

Tetra miniMAX MS

GEMS71-1, GEMS50-1, GEMS41-1, GEMS32-1

Tetra MAX

GEMX71-2, GEMX50-2, GEMX41-2, GEMX32-2

GEMXRD-1, GEMXGL-1, GEMXBL-1

GEMXPO-1

GEMXRC-1

GEMXYG-1

GEMXH71-2, GEMXH50-2, GEMXH41-2, GEMXH32-2

GEMXHRD-1

Tetra PowerMAX

GEPM71-2, GEPM50-2, GEPM41-2, GEPM32-2

Tetra PowerStrip

GESS71-1, GESS50-1, GESS41-1, GESS32-1

GESSH71-1, GESSH50-1, GESSH41-1, GESSH32-1

Tetra miniStrip

GEWHBSP3, GEWWBSP3-50K, GEWWBSP3-41K, GEWWBSP3

GEBSH71-1, GEBSH50-1, GEBSH41-1, GEBSH32-1

GEPS12-60U-NA

Power Supply (12VDC/60W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2

GEPS12-60U-GL

Power Supply (12VDC/60W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2; SELV

GEPS12D-60U

0-10V Dimming Power Supply (12VDC/60W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2

GEPS12W-60

Power Supply (12VDC/60W), Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2

GEPS12W-60M

Power Supply (12VDC/60W) with M20 Connector, Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2



Tetra miniMAX

GEMM71-2, GEMM50-2, GEMM41-2, GEMM32-2

GEMMGL-1,

GEMMBL-1, GEMMRD-1

GEMMPO-1

Tetra miniMAX MS

GEMS71-1, GEMS50-1, GEMS41-1, GEMS32-1

Tetra MAX

GEMX71-2, GEMX50-2, GEMX41-2, GEMX32-2

GEMXBL-1, GEMXRD-1, GEMXGL-1,

GEMXPO-1

GEMXRC-1

GEMXYG-1

GEMXH71-2, GEMXH50-2, GEMXH41-2, GEMXH32-2

GEMXHRD-1

Tetra PowerMAX

GEPM71-2, GEPM50-2, GEPM41-2, GEPM32-2

Tetra PowerStrip

GESS71-1, GESS50-1, GESS41-1, GESS32-1

GESSH71-1, GESSH50-1, GESSH41-1, GESSH32-1

Tetra MiniStrip

GEWHBSP3, GEWWBSP3-50K, GEWWBSP3-41K, GEWWBSP3

GEBSH71-1, GEBSH50-1, GEBSH41-1, GEBSH32-1

Rated Watts	Maximum Load	Power Supply Certifications	Remote Mounting Distance			
			18 AWG	16 AWG	14 AWG	12 AWG
0.324W/module	56 modules/22 ft. (6.70 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.384W/module	50 modules/20 ft. (6.10 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.312W	50 modules/20 ft. (6.10 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.480W/module	40 modules/16 ft. (4.88 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.384W/module	50 modules/20 ft. (6.10 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.456W/module	42 modules/21 ft. (6.40 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.480W/module	40 modules/20 ft. (6.10 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.360W/module	52 modules/26 ft. (7.92 m.)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.288W/module	66 modules/33ft. (10.06 m.)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.540W/module	34 modules/17 ft. (5.18 m.)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.720W/module	26 modules/13 ft. (3.96 m.)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.408W/module	46 modules/23 ft. (7.01 m.)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
1.32W/module	14 modules/9 ft. (2.74 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
2.4W/module	6 modules/6 ft. (1.82 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
3.63W/module	5 modules/5ft. (1.52 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
1.10W/module	17 modules/17 ft. (5.18 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
1.49W/module	12 modules/12 ft. (3.66 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	—	—	—
0.324W	170 modules/68 ft. (20.73 m)	UL/CUL	15 ft./4.6 m	23 ft./7.0 m	38 ft./11.6 m	65 ft./19.8 m
0.312W	150 modules/60 ft. (18.29 m)	UL/CUL	15 ft./4.6 m	23 ft./7.0 m	38 ft./11.6 m	65 ft./19.8 m
0.384W	150 modules/60 ft. (18.29 m)	UL/CUL	15 ft./4.6 m	23 ft./7.0 m	38 ft./11.6 m	65 ft./19.8 m
0.480W	120 modules/48 ft. (14.63 m)	UL/CUL	15 ft./4.6 m	23 ft./7.0 m	38 ft./11.6 m	65 ft./19.8 m
0.384W/module	150 modules/60 ft. (18.29 m)	UL/CUL	30 ft./9.1 m	50 ft./15.2 m	80 ft./24.4 m	120 ft./36.6 m
0.456W/module	128 modules/64 ft. (19.51 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.480W/module	120 modules/60 ft. (18.29 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.360W/module	160 modules/80 ft. (24.38 m.)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.288W/module	200 modules/100 ft. (30.48 m.)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.540W/module	106 modules/53 ft. (16.15 m.)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.720W/module	80 modules/40 ft. (12.20 m.)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
0.408W/module	142 modules/71 ft. (21.64 m.)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
1.32W/module	42 modules/28 ft. (8.53 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.2 m
2.4W/module	20 modules/20.0 ft. (6.01 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
3.63W/module	16 modules/16.0 ft. (4.88 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
1.10W/module	53 modules/53 ft. (16.16 m)	CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
1.49W/module	38 modules/38 ft. (11.58 m)	CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m

Tetra® Power Supplies — 24 Volt

SKU	Description	Supports Tetra Products	SKUs
GEPS24-20 	Power Supply (24VDC/20W), Input Voltage: 90-264VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2	Tetra PowerStrip DS	GEDS71-1, GEDS50-1, GEDS41-1, GEDS32-1 GEDSH71-1, GEDSH50-1, GEDSH41-1, GEDSH32-1
		Tetra miniStrip DS	GEWHBDP6, GEWWBDP6-50K, GEWWBDP6-41K, GEWWBDP6 GEBDH71-1, GEBDH50-1, GEBDH41-1, GEBDH32-1
		Tetra EdgeStrip	GEWHBIP2, GEWWBIP2-50K, GEWWBIP2-41K, GEWWBIP2 GEBIH71-1, GEBIH50-1, GEBIH41-1, GEBIH32-1
		Tetra Contour LS	GEXNLRD-1 GEXNLBL-1, GEXNLGL-1 GEXNL65-1, GEXNL32-1
		Tetra Contour	GEXNBL-1, GEXNGL-1, GEXNRD-1 GEXNYG-1, GEXNRC-1 GEXN65-1, GEXN32-1
GEPS24D-80U GEPS24W-80 GEPS24W-80M 	GEPS24D-80U 0-10V Dimming Power Supply (24VDC/80W), Input Voltage: 90-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2 GEPS24W-80 Power Supply (24VDC/80W), Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2 GEPS24W-80M Power Supply (24VDC/80W), Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2	Tetra PowerStrip DS	GEDS71-1, GEDS50-1, GEDS41-1, GEDS32-1 GEDSH71-1, GEDSH50-1, GEDSH41-1, GEDSH32-1
		Tetra miniStrip DS	GEWHBDP6, GEWWBDP6-50K, GEWWBDP6-41K, GEWWBDP6 GEBDH71-1, GEBDH50-1, GEBDH41-1, GEBDH32-1
		Tetra EdgeStrip	GEWHBIP2, GEWWBIP2-50K, GEWWBIP2-41K, GEWWBIP2 GEBIH71-1, GEBIH50-1, GEBIH41-1, GEBIH32-1
		Tetra Contour LS	GEXNLRD-1 GEXNLBL-1, GEXNLGL-1 GEXNL65-1, GEXNL32-1
		Tetra Contour	GEXNBL-1, GEXNGL-1, GEXNRD-1 GEXNYG-1, GEXNRC-1 GEXN65-1, GEXN32-1
GEPS24-100U-NA GEPS24-100U-GL 	GEPS24-100U-NA Power Supply (24VDC / 96W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2 GEPS24-100U-GL Power Supply (24VDC / 96W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2	Tetra PowerStrip DS	GEDS71-1, GEDS50-1, GEDS41-1, GEDS32-1 GEDSH71-1, GEDSH50-1, GEDSH41-1, GEDSH32-1
		Tetra miniStrip DS	GEWHBDP6, GEWWBDP6-50K, GEWWBDP6-41K, GEWWBDP6 GEBDH71-1, GEBDH50-1, GEBDH41-1, GEBDH32-1
		Tetra EdgeStrip	GEWHBIP2, GEWWBIP2-50K, GEWWBIP2-41K, GEWWBIP2 GEBIH71-1, GEBIH50-1, GEBIH41-1, GEBIH32-1
		Tetra Contour LS	GEXNLRD-1 GEXNLBL-1, GEXNLGL-1 GEXNL65-1, GEXNL32-1
		Tetra Contour	GEXNBL-1, GEXNGL-1, GEXNRD-1 GEXNYG-1, GEXNRC-1 GEXN65-1, GEXN32-1
GEPS24-180U 	Power Supply (24VDC/180W), Input Voltage: 90-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 2 Output Banks; Class 2	Tetra PowerStrip DS	GEDS71-1, GEDS50-1, GEDS41-1, GEDS32-1 GEDSH71-1, GEDSH50-1, GEDSH41-1, GEDSH32-1
		Tetra miniStrip DS	GEWHBDP6, GEWWBDP6-50K, GEWWBDP6-41K, GEWWBDP6 GEBDH71-1, GEBDH50-1, GEBDH41-1, GEBDH32-1
		Tetra EdgeStrip	GEWHBIP2, GEWWBIP2-50K, GEWWBIP2-41K, GEWWBIP2 GEBIH71-1, GEBIH50-1, GEBIH41-1, GEBIH32-1
		Tetra Contour LS	GEXNLRD-1 GEXNLBL-1, GEXNLGL-1 GEXNL65-1, GEXNL32-1
		Tetra Contour	GEXNBL-1, GEXNGL-1, GEXNRD-1 GEXNYG-1, GEXNRC-1 GEXN65-1, GEXN32-1

Rated Watts	Maximum Load	Power Supply Certifications	Remote Mounting Distance			
			18 AWG	16 AWG	14 AWG	12 AWG
4.8W/module	3 modules/3 ft. (0.91 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
6.55W/module	3 modules/3 ft. (0.91 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
2.20W/module	8 modules/8 ft. (2.44 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
2.98W/module	6 modules/6 ft. (1.83 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
2.40W/module	7 modules/4.67 ft. (1.42 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
5.40W/module	3 modules/2 ft. (0.61 m)	UL/CUL, CE, C-Tick, PSE	30 ft./9.1 m	-	-	-
1.30W/ft. (strip)	14 ft. (4.27 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
1.73W/ft. (strip)	11 ft. (3.35 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
3.17W/ft. (strip)	6 ft. (1.83 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
1.52W/ft. (Strip)	12 ft. (3.66 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
2.27W/ft. (Strip)	8 ft. (2.44 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
3.17W/ft. (Strip)	6 ft. (1.83 m)	UL/CUL, CE, C-Tick, PSE	20 ft./6.1 m	-	-	-
4.8W/module	14 modules/14 ft. (4.27 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
6.55W/module	12 modules/12 ft. (3.66 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.20W/module	31 modules/31 ft. (9.45 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.98W/module	24 modules/24 ft. (7.32 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.40W/module	30 modules/20 ft. (6.1 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
5.40W/module	14 modules/9.3 ft. (2.84 m)	UL/CUL, CE, PSE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
1.30W/ft. (strip)	58 ft. (17.68 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.73W/ft. (strip)	44 ft. (13.41 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (strip)	24 ft. (7.3 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.52W/ft. (Strip)	50 ft. (15.24 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
2.27W/ft. (Strip)	33 ft. (10.06 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (Strip)	24 ft. (7.3 m)	UL/CUL, CE, PSE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
4.8W/module	16 modules/16.0 ft. (4.88 m)	UL/CUL	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
6.55W/module	13 modules/13 ft. (3.96m)	UL/CUL	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.20W/module	39 modules/39 ft. (11.89 m)	UL/CUL	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.98W/module	30 modules/30 ft. (9.14 m)	UL/CUL	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.40W/module	36 modules/24 ft. (7.32 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
5.40W/module	17 modules/11.33 ft. (3.45 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
1.30W/ft. (strip)	69 ft. (21m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.73W/ft. (strip)	52 ft. (15.85m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (strip)	29 ft. (8.8m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.52W/ft. (Strip)	59 ft. (17.9 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
2.27W/ft. (Strip)	40 ft. (12.19 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (Strip)	29 ft. (8.8 m)	UL/CUL, CE, C-Tick, SELV	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
4.8W/module	14 modules/14 ft. (4.27 m) per bank; 28 modules/28 ft. (8.53 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
6.55W/module	13 modules/13 ft. (3.96 m) per bank; 26 modules/26 ft. (7.92 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.20W/module	35 modules/35 ft. (10.67 m) per bank; 70 modules/70 ft. (21.34 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.98W/module	27 modules/27 ft. (8.23 m) per bank; 54 modules/54 ft. (16.46 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
2.40W/module	33 modules/22 ft. (6.71 m) per bank; 66 modules/44 ft. (13.42 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
5.40W/module	16 modules/10.67 ft. (3.25 m) per bank; 32 modules/21 ft. (6.5 m) per PS	UL/CUL, CE	20 ft./6.1 m	25 ft./7.6 m	35 ft./10.6 m	40 ft./12.1 m
1.30W/ft. (strip)	65 ft. (19.81 m) per output channel; 130 ft. (39.62 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.73W/ft. (strip)	48 ft. (14.63 m) per output channel; 96 ft. (29.26 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (strip)	27 ft. (8.2 m) per output channel; 54 ft. (16.4 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
1.52W/ft. (Strip)	55 ft. (16.76 m) per output channel; 110 ft. (33.53 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
2.27W/ft. (Strip)	37 ft. (11.28 m) per output channel; 74 ft. (22.55 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m
3.17W/ft. (Strip)	27 ft. (8.2 m) per output channel; 54 ft. (16.4 m) per PS	UL/CUL, CE	20 ft./6.1 m	30 ft./9.1 m	50 ft./15.2 m	86 ft./26.1 m

Tetra® Power Supplies — 24 Volt

LineFit Light LED



SKU	Description	SKUs	Rated Watts	Maximum Load
GEPS24D-80U	0-10V Dimming Power Supply (24VDC/80W), Input Voltage: 90-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2	GEF18T12SGNHOLED, GEF18T12DHOLED, GEF18T12CWHOLED	7.2W/bar	12 ft
		GEF24T12SGNHOLED, GEF24T12DHOLED, GEF24T12CWHOLED	11.5W/bar	12 ft
		GEF30T12SGNHOLED, GEF30T12DHOLED, GEF30T12CWHOLED	14.4W/bar	12 ft
GEPS24W-80	Power Supply (24VDC/80W), Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2	GEF36T12SGNHOLED, GEF36T12DHOLED, GEF36T12CWHOLED	17.3W/bar	12 ft
		GEF42T12SGNHOLED, GEF42T12DHOLED, GEF42T12CWHOLED	20.2W/bar	12 ft
		GEF48T12SGNHOLED, GEF48T12DHOLED, GEF48T12CWHOLED	23.0W/bar	12 ft
GEPS24W-80M	Power Supply (24VDC/80W), Input Voltage: 90-264VAC; Wet Location Rated; 1 Output Bank; Class 2	GEF60T12SGNHOLED, GEF60T12DHOLED, GEF60T12CWHOLED	28.8W/bar	12 ft
		GEF64T12SGNHOLED, GEF64T12DHOLED, GEF64T12CWHOLED	30.2W/bar	12 ft
		GEF72T12SGNHOLED, GEF72T12DHOLED, GEF72T12CWHOLED	34.6W/bar	12 ft
GEPS24-100U-NA	Power Supply (24VDC / 96W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2	GEF84T12SGNHOLED, GEF84T12DHOLED, GEF84T12CWHOLED	40.3W/bar	12 ft
		GEF96T12SGNHOLED, GEF96T12DHOLED, GEF96T12CWHOLED	46.1W/bar	12 ft
		GEF18T12SGNHOLED, GEF18T12DHOLED, GEF18T12CWHOLED	7.2W/bar	16 ft.
GEPS24-100U-GL	Power Supply (24VDC / 96W), Input Voltage: 108-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 1 Output Bank; Class 2	GEF24T12SGNHOLED, GEF24T12DHOLED, GEF24T12CWHOLED	11.5W/bar	16 ft.
		GEF30T12SGNHOLED, GEF30T12DHOLED, GEF30T12CWHOLED	14.4W/bar	16 ft.
		GEF36T12SGNHOLED, GEF36T12DHOLED, GEF36T12CWHOLED	17.3W/bar	16 ft.
GEPS24-180U	Power Supply (24VDC/180W), Input Voltage: 90-305VAC; Damp Rated; Self-Contained, Remote or Raceway; 2 Output Banks; Class 2	GEF42T12SGNHOLED, GEF42T12DHOLED, GEF42T12CWHOLED	20.2W/bar	16 ft.
		GEF48T12SGNHOLED, GEF48T12DHOLED, GEF48T12CWHOLED	23.0W/bar	16 ft.
		GEF60T12SGNHOLED, GEF60T12DHOLED, GEF60T12CWHOLED	28.8W/bar	16 ft.
		GEF64T12SGNHOLED, GEF64T12DHOLED, GEF64T12CWHOLED	30.2W/bar	16 ft.
		GEF72T12SGNHOLED, GEF72T12DHOLED, GEF72T12CWHOLED	34.6W/bar	16 ft.
		GEF84T12SGNHOLED, GEF84T12DHOLED, GEF84T12CWHOLED	40.3W/bar	16 ft.
		GEF96T12SGNHOLED, GEF96T12DHOLED, GEF96T12CWHOLED	46.1W/bar	16 ft.
		GEF18T12SGNHOLED, GEF18T12DHOLED, GEF18T12CWHOLED	7.2W/bar	14 ft. per bank
		GEF24T12SGNHOLED, GEF24T12DHOLED, GEF24T12CWHOLED	11.5W/bar	14 ft. per bank
		GEF30T12SGNHOLED, GEF30T12DHOLED, GEF30T12CWHOLED	14.4W/bar	14 ft. per bank
		GEF36T12SGNHOLED, GEF36T12DHOLED, GEF36T12CWHOLED	17.3W/bar	14 ft. per bank
		GEF42T12SGNHOLED, GEF42T12DHOLED, GEF42T12CWHOLED	20.2W/bar	14 ft. per bank
		GEF48T12SGNHOLED, GEF48T12DHOLED, GEF48T12CWHOLED	23.0W/bar	14 ft. per bank
		GEF60T12SGNHOLED, GEF60T12DHOLED, GEF60T12CWHOLED	28.8W/bar	14 ft. per bank
		GEF64T12SGNHOLED, GEF64T12DHOLED, GEF64T12CWHOLED	30.2W/bar	14 ft. per bank
		GEF72T12SGNHOLED, GEF72T12DHOLED, GEF72T12CWHOLED	34.6W/bar	14 ft. per bank
		GEF84T12SGNHOLED, GEF84T12DHOLED, GEF84T12CWHOLED	40.3W/bar	14 ft. per bank
		GEF96T12SGNHOLED, GEF96T12DHOLED, GEF96T12CWHOLED	46.1W/bar	14 ft. per bank



GE Lighting • 1-888-MY-GE-LED (1-888-69-43-533) • www.gelighting.com

GE Lighting Solutions, LLC is a subsidiary of the General Electric Company. Tetra is a trademark of GE Lighting Solutions, LLC. The GE brand and logo are trademarks of the General Electric Company.
© 2014 GE Lighting Solutions, LLC. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.